

**Fontconfig Developers Reference, Version  
2.6.99.behdad.20090508**

**Keith Packard**  
HP Cambridge Research Lab

**Table of Contents**

DESCRIPTION .....3  
FUNCTIONAL OVERVIEW.....3  
Datatypes.....4  
FUNCTIONS .....8



## DESCRIPTION

Fontconfig is a library designed to provide system-wide font configuration, customization and application access.

## FUNCTIONAL OVERVIEW

Fontconfig contains two essential modules, the configuration module which builds an internal configuration from XML files and the matching module which accepts font patterns and returns the nearest matching font.

## FONT CONFIGURATION

The configuration module consists of the FcConfig datatype, libexpat and FcConfigParse which walks over an XML tree and amends a configuration with data found within. From an external perspective, configuration of the library consists of generating a valid XML tree and feeding that to FcConfigParse. The only other mechanism provided to applications for changing the running configuration is to add fonts and directories to the list of application-provided font files.

The intent is to make font configurations relatively static, and shared by as many applications as possible. It is hoped that this will lead to more stable font selection when passing names from one application to another. XML was chosen as a configuration file format because it provides a format which is easy for external agents to edit while retaining the correct structure and syntax.

Font configuration is separate from font matching; applications needing to do their own matching can access the available fonts from the library and perform private matching. The intent is to permit applications to pick and choose appropriate functionality from the library instead of forcing them to choose between this library and a private configuration mechanism. The hope is that this will ensure that configuration of fonts for all applications can be centralized in one place. Centralizing font configuration will simplify and regularize font installation and customization.

## FONT PROPERTIES

While font patterns may contain essentially any properties, there are some well known properties with associated types. Fontconfig uses some of these properties for font matching and font completion. Others are provided as a convenience for the applications rendering mechanism.

Property Definitions

Property	CPP Symbol	Type	Description
family	FC_FAMILY	String	Font family names
familylang	FC_FAMILYLANG	String	Language cooresponding to each family name
style	FC_STYLE	String	Font style. Overrides weight and slant
stylelang	FC_STYLELANG	String	Language cooresponding to each style name
fullname	FC_FULLNAME	String	Font face full name where different from family and family + style
fullnamelang	FC_FULLNAMELANG	String	Language cooresponding to each fullname
slant	FC_SLANT	Int	Italic, oblique or roman
weight	FC_WEIGHT	Int	Light, medium, demibold, bold or black

size	FC_SIZE	Double	Point size
width	FC_WIDTH	Int	Condensed, normal or expanded
aspect	FC_ASPECT	Double	Stretches glyphs horizontally before hinting
pixelsize	FC_PIXEL_SIZE	Double	Pixel size
spacing	FC_SPACING	Int	Proportional, dual-width, monospace or charcell
foundry	FC_FOUNDRY	String	Font foundry name
antialias	FC_ANTIALIAS	Bool	Whether glyphs can be antialiased
hinting	FC_HINTING	Bool	Whether the rasterizer should use hinting
hintstyle	FC_HINT_STYLE	Int	Automatic hinting style
verticallayout	FC_VERTICAL_LAYOUT	Bool	Use vertical layout
autohint	FC_AUTOHINT	Bool	Use autohinter instead of normal hinter
globaladvance	FC_GLOBAL_ADVANCE	Bool	Use font global advance data
file	FC_FILE	String	The filename holding the font
index	FC_INDEX	Int	The index of the font within the file
ftface	FC_FT_FACE	FT_Face	Use the specified FreeType face object
rasterizer	FC_RASTERIZER	String	Which rasterizer is in use
outline	FC_OUTLINE	Bool	Whether the glyphs are outlines
scalable	FC_SCALABLE	Bool	Whether glyphs can be scaled
scale	FC_SCALE	Double	Scale factor for point->pixel conversions
dpi	FC_DPI	Double	Target dots per inch
rgba	FC_RGBA	Int	unknown, rgb, bgr, vrgb, vbgr, none - subpixel geometry
lcdfilter	FC_LCD_FILTER	Int	Type of LCD filter
minspace	FC_MINSPACE	Bool	Eliminate leading from line spacing
charset	FC_CHARSET	CharSet	Unicode chars encoded by the font
lang	FC_LANG	LangSet	Set of RFC-3066-style languages this font supports
fontversion	FC_FONTVERSION	Int	Version number of the font
capability	FC_CAPABILITY	String	List of layout capabilities in the font
embolden	FC_EMBOLDEN	Bool	Rasterizer should synthetically embolden the font

## Datatypes

Fontconfig uses abstract datatypes to hide internal implementation details for most data structures. A few structures are exposed where appropriate.

### FcChar8, FcChar16, FcChar32, FcBool

These are primitive datatypes; the FcChar\* types hold precisely the number of bits stated (if supported by the C implementation). FcBool holds one of two CPP symbols: FcFalse or FcTrue.

## FcMatrix

An FcMatrix holds an affine transformation, usually used to reshape glyphs. A small set of matrix operations are provided to manipulate these.

```
typedef struct _FcMatrix {
    double xx, xy, yx, yy;
} FcMatrix;
```

## FcCharSet

An FcCharSet is an abstract type that holds the set of encoded unicode chars in a font. Operations to build and compare these sets are provided.

## FcLangSet

An FcLangSet is an abstract type that holds the set of languages supported by a font. Operations to build and compare these sets are provided. These are computed for a font based on orthographic information built into the fontconfig library. Fontconfig has orthographies for all of the ISO 639-1 languages except for MS, NA, PA, PS, QU, RN, RW, SD, SG, SN, SU and ZA. If you have orthographic information for any of these languages, please submit them.

## FcLangResult

An FcLangResult is an enumeration used to return the results of comparing two language strings or FcLangSet objects. FcLangEqual means the objects match language and territory. FcLangDifferentTerritory means the objects match in language but differ in territory. FcLangDifferentLang means the objects differ in language.

## FcType

Tags the kind of data stored in an FcValue.

## FcValue

An FcValue object holds a single value with one of a number of different types. The 'type' tag indicates which member is valid.

```
typedef struct _FcValue {
    FcType type;
    union {
        const FcChar8 *s;
        int i;
        FcBool b;
        double d;
        const FcMatrix *m;
        const FcCharSet *c;
    } u;
} FcValue;
```

## FcValue Members

Type	Union member	Datatype
-----	-----	-----
FcTypeVoid	(none)	(none)
FcTypeInteger	i	int
FcTypeDouble	d	double
FcTypeString	s	FcChar8 *
FcTypeBool	b	b
FcTypeMatrix	m	FcMatrix *
FcTypeCharSet	c	FcCharSet *
FcTypeFTFace f	void * (FT_Face)	
FcTypeLangSet l	FcLangSet *	

**FcPattern**

holds a set of names with associated value lists; each name refers to a property of a font. FcPatterns are used as inputs to the matching code as well as holding information about specific fonts. Each property can hold one or more values; conventionally all of the same type, although the interface doesn't demand that.

**FcFontSet**

```
typedef struct _FcFontSet {
    int nfont;
    int sfont;
    FcPattern **fonts;
} FcFontSet;
```

An FcFontSet contains a list of FcPatterns. Internally fontconfig uses this data structure to hold sets of fonts. Externally, fontconfig returns the results of listing fonts in this format. 'nfont' holds the number of patterns in the 'fonts' array; 'sfont' is used to indicate the size of that array.

**FcStrSet, FcStrList**

FcStrSet holds a list of strings that can be appended to and enumerated. Its unique characteristic is that the enumeration works even while strings are appended during enumeration. FcStrList is used during enumeration to safely and correctly walk the list of strings even while that list is edited in the middle of enumeration.

**FcObjectSet**

```
typedef struct _FcObjectSet {
    int nobject;
    int sobject;
    const char **objects;
} FcObjectSet;
```

holds a set of names and is used to specify which fields from fonts are placed in the the list of returned patterns when listing fonts.

## FcObjectType

```
typedef struct _FcObjectType {
    const char *object;
    FcType type;
} FcObjectType;
```

marks the type of a pattern element generated when parsing font names. Applications can add new object types so that font names may contain the new elements.

## FcConstant

```
typedef struct _FcConstant {
    const FcChar8 *name;
    const char *object;
    int value;
} FcConstant;
```

Provides for symbolic constants for new pattern elements. When 'name' is seen in a font name, an 'object' element is created with value 'value'.

## FcBlanks

holds a list of Unicode chars which are expected to be blank; unexpectedly blank chars are assumed to be invalid and are elided from the charset associated with the font.

## FcFileCache

holds the per-user cache information for use while loading the font database. This is built automatically for the current configuration when that is loaded. Applications must always pass '0' when one is requested.

## FcConfig

holds a complete configuration of the library; there is one default configuration, other can be constructed from XML data structures. All public entry points that need global data can take an optional FcConfig\* argument; passing 0 uses the default configuration. FcConfig objects hold two sets of fonts, the first contains those specified by the configuration, the second set holds those added by the application at run-time. Interfaces that need to reference a particular set use one of the FcSetName enumerated values.

## FcSetName

Specifies one of the two sets of fonts available in a configuration; FcSetSystem for those fonts specified in the configuration and FcSetApplication which holds fonts provided by the application.

## FcResult

Used as a return type for functions manipulating FcPattern objects.

FcResult Values	
Result Code	Meaning
-----	
FcResultMatch	Object exists with the specified ID
FcResultNoMatch	Object doesn't exist at all
FcResultTypeMismatch	Object exists, but the type doesn't match
FcResultNoId	Object exists, but has fewer values than specified
FcResultOutOfMemory	Malloc failed

## FcAtomic

Used for locking access to config files. Provides a safe way to update configuration files.

## FcCache

Holds information about the fonts contained in a single directory. Normal applications need not worry about this as caches for font access are automatically managed by the library. Applications dealing with cache management may want to use some of these objects in their work, however the included 'fc-cache' program generally suffices for all of that.

## FUNCTIONS

These are grouped by functionality, often using the main datatype being manipulated.

### Initialization

These functions provide some control over how the library is initialized.

## FcInitLoadConfig

### Name

FcInitLoadConfig — load configuration

### Synopsis

```
#include <fontconfig.h>

FcConfig * FcInitLoadConfig(void);
```



## Description

Loads the default configuration file and returns the resulting configuration. Does not load any font information.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcInitLoadConfigAndFonts

## Name

FcInitLoadConfigAndFonts — load configuration and font data

## Synopsis

```
#include <fontconfig.h>

FcConfig * FcInitLoadConfigAndFonts(void);
```

## Description

Loads the default configuration file and builds information about the available fonts. Returns the resulting configuration.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcInit

## Name

FcInit — initialize fontconfig library

## Synopsis

```
#include <fontconfig.h>

FcBool FcInit(void);
```

## Description

Loads the default configuration file and the fonts referenced therein and sets the default configuration to that result. Returns whether this process succeeded or not. If the default configuration has already been loaded, this routine does nothing and returns `FcTrue`.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcFini

### Name

`FcFini` — finalize fontconfig library

### Synopsis

```
#include <fontconfig.h>

void FcFini(void);
```

### Description

Frees all data structures allocated by previous calls to fontconfig functions. Fontconfig returns to an uninitialized state, requiring a new call to one of the `FcInit` functions before any other fontconfig function may be called.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcGetVersion

### Name

`FcGetVersion` — library version number

## Synopsis

```
#include <fontconfig.h>

int FcGetVersion(void);
```

## Description

Returns the version number of the library.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcInitReinitialize

### Name

FcInitReinitialize — re-initialize library

### Synopsis

```
#include <fontconfig.h>

FcBool FcInitReinitialize(void);
```

### Description

Forces the default configuration file to be reloaded and resets the default configuration. Returns FcFalse if the configuration cannot be reloaded (due to config file errors, allocation failures or other issues) and leaves the existing configuration unchanged. Otherwise returns FcTrue.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcInitBringUptoDate

### Name

FcInitBringUptoDate — reload configuration files if needed

### Synopsis

```
#include <fontconfig.h>

FcBool FcInitBringUptoDate(void);
```

### Description

Checks the rescan interval in the default configuration, checking the configuration if the interval has passed and reloading the configuration if when any changes are detected. Returns FcFalse if the configuration cannot be reloaded (see FcInitReinitialize). Otherwise returns FcTrue.

### Version

Fontconfig version 2.6.99.behdad.20090508

### FcPattern

An FcPattern is an opaque type that holds both patterns to match against the available fonts, as well as the information about each font.

## FcPatternCreate

### Name

FcPatternCreate — Create a pattern

### Synopsis

```
#include <fontconfig.h>

FcPattern * FcPatternCreate(void);
```

## Description

Creates a pattern with no properties; used to build patterns from scratch.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternDuplicate

### Name

FcPatternDuplicate — Copy a pattern

### Synopsis

```
#include <fontconfig.h>

FcPattern * FcPatternDuplicate(const FcPattern *p);
```

### Description

Copy a pattern, returning a new pattern that matches *p*. Each pattern may be modified without affecting the other.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternReference

### Name

FcPatternReference — Increment pattern reference count

### Synopsis

```
#include <fontconfig.h>

void FcPatternReference(FcPattern *p);
```

## Description

Add another reference to *p*. Patterns are freed only when the reference count reaches zero.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcPatternDestroy

## Name

FcPatternDestroy — Destroy a pattern

## Synopsis

```
#include <fontconfig.h>

void FcPatternDestroy(FcPattern *p);
```

## Description

Decrement the pattern reference count. If all references are gone, destroys the pattern, in the process destroying all related values.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcPatternEqual

## Name

FcPatternEqual — Compare patterns

## Synopsis

```
#include <fontconfig.h>

FcBool FcPatternEqual(const FcPattern *pa, const FcPattern *pb);
```

## Description

Returns whether *pa* and *pb* are exactly alike.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcPatternEqualSubset

## Name

FcPatternEqualSubset — Compare portions of patterns

## Synopsis

```
#include <fontconfig.h>

FcBool FcPatternEqualSubset(const FcPattern *pa, const FcPattern *pb,
const FcObjectSet *os);
```

## Description

Returns whether *pa* and *pb* have exactly the same values for all of the objects in *os*.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcPatternFilter

## Name

FcPatternFilter — Filter the objects of pattern

## Synopsis

```
#include <fontconfig.h>

FcPattern * FcPatternFilter(FcPattern *p, const FcObjectSet *);
```

## Description

Returns a new pattern that only has those objects from  $p$  that are in  $os$ . If  $os$  is NULL, a duplicate of  $p$  is returned.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternHash

### Name

FcPatternHash — Compute a pattern hash value

### Synopsis

```
#include <fontconfig.h>

FcChar32 FcPatternHash(const FcPattern *p);
```

### Description

Returns a 32-bit number which is the same for any two patterns which are equal.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternAdd

### Name

FcPatternAdd — Add a value to a pattern

### Synopsis

```
#include <fontconfig.h>

FcBool FcPatternAdd(FcPattern *p, const char *object, FcValue value,
FcBool append);
```



## Description

Adds a single value to the list of values associated with the property named 'object'. If 'append' is FcTrue, the value is added at the end of any existing list, otherwise it is inserted at the beginning. 'value' is saved (with FcValueSave) when inserted into the pattern so that the library retains no reference to any application-supplied data structure.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternAddWeak

### Name

FcPatternAddWeak — Add a value to a pattern with weak binding

### Synopsis

```
#include <fontconfig.h>
```

```
FcBool FcPatternAddWeak(FcPattern *p, const char *object, FcValue  
value, FcBool append);
```

### Description

FcPatternAddWeak is essentially the same as FcPatternAdd except that any values added to the list have binding *weak* instead of *strong*.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternAdd-Type

### Name

FcPatternAddInteger, FcPatternAddDouble, FcPatternAddString,  
FcPatternAddMatrix, FcPatternAddCharSet, FcPatternAddBool,  
FcPatternAddFTFace, FcPatternAddLangSet — Add a typed value to a  
pattern

## Synopsis

```
#include <fontconfig.h>

FcBool FcPatternAddInteger(FcPattern *p, const char *object, int i);
FcBool FcPatternAddDouble(FcPattern *p, const char *object, double d);
FcBool FcPatternAddString(FcPattern *p, const char *object, const
FcChar8 *s);
FcBool FcPatternAddMatrix(FcPattern *p, const char *object, const
FcMatrix *m);
FcBool FcPatternAddCharSet(FcPattern *p, const char *object, const
FcCharSet *c);
FcBool FcPatternAddBool(FcPattern *p, const char *object, FcBool b);
FcBool FcPatternAddFTFace(FcPattern *p, const char *object, const
FT_Face f);
FcBool FcPatternAddLangSet(FcPattern *p, const char *object, const
FcLangSet *l);
```

## Description

These are all convenience functions that insert objects of the specified type into the pattern. Use these in preference to `FcPatternAdd` as they will provide compile-time typechecking. These all append values to any existing list of values.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternGet

### Name

`FcPatternGet` — Return a value from a pattern

## Synopsis

```
#include <fontconfig.h>

FcResult FcPatternGet(FcPattern *p, const char *object, int id,
FcValue *v);
```

## Description

Returns in `v` the `id`'th value associated with the property `object`. The value returned is not a copy, but rather refers to the data stored within the pattern directly. Applications must not free this value.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternGet-Type

### Name

FcPatternGetInteger, FcPatternGetDouble, FcPatternGetString, FcPatternGetMatrix, FcPatternGetCharSet, FcPatternGetBool, FcPatternGetFTFace, FcPatternGetLangSet — Return a typed value from a pattern

### Synopsis

```
#include <fontconfig.h>

FcResult FcPatternGetInteger(FcPattern *p, const char *object, int n,
int *i);
FcResult FcPatternGetDouble(FcPattern *p, const char *object, int n,
double *d);
FcResult FcPatternGetString(FcPattern *p, const char *object, int n,
FcChar8 **s);
FcResult FcPatternGetMatrix(FcPattern *p, const char *object, int n,
FcMatrix **s);
FcResult FcPatternGetCharSet(FcPattern *p, const char *object, int n,
FcCharSet **c);
FcResult FcPatternGetBool(FcPattern *p, const char *object, int n,
FcBool *b);
FcResult FcPatternGetFTFace(FcPattern *p, const char *object, int n);
FcResult FcPatternGetLangSet(FcPattern *p, const char *object, FT_Face
*f);
```

### Description

These are convenience functions that call FcPatternGet and verify that the returned data is of the expected type. They return FcResultTypeMismatch if this is not the case. Note that these (like FcPatternGet) do not make a copy of any data structure referenced by the return value. Use these in preference to FcPatternGet to provide compile-time typechecking.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternBuild

### Name

FcPatternBuild, FcPatternVaBuild, FcPatternVapBuild — Create patterns from arguments

### Synopsis

```
#include <fontconfig.h>

FcPattern * FcPatternBuild(FcPattern *pattern, ...);
FcPattern * FcPatternVaBuild(FcPattern *pattern, va_list va);
void FcPatternVapBuild(FcPattern *result, FcPattern *pattern, va_list
va);
```

### Description

Builds a pattern using a list of objects, types and values. Each value to be entered in the pattern is specified with three arguments:

1. Object name, a string describing the property to be added.
2. Object type, one of the FcType enumerated values
3. Value, not an FcValue, but the raw type as passed to any of the FcPatternAdd<type> functions. Must match the type of the second argument.

The argument list is terminated by a null object name, no object type nor value need be passed for this. The values are added to 'pattern', if 'pattern' is null, a new pattern is created. In either case, the pattern is returned. Example

```
pattern = FcPatternBuild (0, FC_FAMILY, FcTypeString, "Times", (char *) 0);
```

FcPatternVaBuild is used when the arguments are already in the form of a varargs value. FcPatternVapBuild is a macro version of FcPatternVaBuild which returns its result directly in the *result* variable.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternDel

### Name

FcPatternDel — Delete a property from a pattern

## Synopsis

```
#include <fontconfig.h>

FcBool FcPatternDel(FcPattern *p, const char *object);
```

## Description

Deletes all values associated with the property 'object', returning whether the property existed or not.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternRemove

### Name

FcPatternRemove — Remove one object of the specified type from the pattern

## Synopsis

```
#include <fontconfig.h>

FcBool FcPatternRemove(FcPattern *p, const char *object, int id);
```

## Description

Removes the value associated with the property 'object' at position 'id', returning whether the property existed and had a value at that position or not.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternPrint

### Name

FcPatternPrint — Print a pattern for debugging

## Synopsis

```
#include <fontconfig.h>

void FcPatternPrint(const FcPattern *p);
```

## Description

Prints an easily readable version of the pattern to stdout. There is no provision for reparsing data in this format, it's just for diagnostics and debugging.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcDefaultSubstitute

## Name

FcDefaultSubstitute — Perform default substitutions in a pattern

## Synopsis

```
#include <fontconfig.h>

void FcDefaultSubstitute(FcPattern *pattern);
```

## Description

Supplies default values for underspecified font patterns:

- Patterns without a specified style or weight are set to Medium
- Patterns without a specified style or slant are set to Roman
- Patterns without a specified pixel size are given one computed from any specified point size (default 12), dpi (default 75) and scale (default 1).

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcNameParse

### Name

FcNameParse — Parse a pattern string

### Synopsis

```
#include <fontconfig.h>

FcPattern * FcNameParse(const FcChar8 *name);
```

### Description

Converts *name* from the standard text format described above into a pattern.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcNameUnparse

### Name

FcNameUnparse — Convert a pattern back into a string that can be parsed

### Synopsis

```
#include <fontconfig.h>

FcChar8 * FcNameUnparse(FcPattern *pat);
```

### Description

Converts the given pattern into the standard text format described above. The return value is not static, but instead refers to newly allocated memory which should be freed by the caller using `free()`.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcPatternFormat

### Name

`FcPatternFormat` — Format a pattern into a string according to a format specifier

### Synopsis

```
#include <fontconfig.h>
```

```
FcChar8 * FcPatternFormat (FcPattern *pat, const FcChar8 *format);
```

### Description

Converts given pattern *pat* into text described by the format specifier *format*. The return value refers to newly allocated memory which should be freed by the caller using `free()`, or `NULL` if *format* is invalid.

The format is loosely modelled after `printf`-style format string. The format string is composed of zero or more directives: ordinary characters (not "%"), which are copied unchanged to the output stream; and tags which are interpreted to construct text from the pattern in a variety of ways (explained below). Special characters can be escaped using backslash. C-string style special characters like `\n` and `\r` are also supported (this is useful when the format string is not a C string literal). It is advisable to always escape curly braces that are meant to be copied to the output as ordinary characters.

Each tag is introduced by the character "%", followed by an optional minimum field width, followed by tag contents in curly braces (`{}`). If the minimum field width value is provided the tag will be expanded and the result padded to achieve the minimum width. If the minimum field width is positive, the padding will right-align the text. Negative field width will left-align. The rest of this section describes various supported tag contents and their expansion.

A *simple* tag is one where the content is an identifier. When simple tags are expanded, the named identifier will be looked up in *pattern* and the resulting list of values returned, joined together using comma. For example, to print the family name and style the pattern, use the format `"%{family} %{style}\n"`. To extend the family column to forty characters use `"%-40{family}%{style}\n"`.

Simple tags expand to list of all values for an element. To only choose one of the values, one can index using the syntax `"%{elt[idx]}"`. For example, to get the first family name only, use `"%{family[0]}"`.

If a simple tag ends with `"="` and the element is found in the pattern, the name of the element followed by `"="` will be output before the list of values. For example, `"%{weight=}"` may expand to the string `"weight=80"`. Or to the empty string if *pattern* does not have weight set.

If a simple tag starts with `":"` and the element is found in the pattern, `":"` will be printed first. For example, combining this with the `=`, the format `"%{:weight=}"` may expand to `":weight=80"` or to the empty string if *pattern* does not have weight set.



If a simple tag contains the string ":-", the rest of the the tag contents will be used as a default string. The default string is output if the element is not found in the pattern. For example, the format "%{:weight=:-123}" may expand to ":weight=80" or to the string ":weight=123" if *pattern* does not have weight set.

A *count* tag is one that starts with the character "#" followed by an element name, and expands to the number of values for the element in the pattern. For example, "%{#family}" expands to the number of family names *pattern* has set, which may be zero.

A *sub-expression* tag is one that expands a sub-expression. The tag contents are the sub-expression to expand placed inside another set of curly braces. Sub-expression tags are useful for aligning an entire sub-expression, or to apply converters (explained later) on an entire sub-expression. For example, the format "%40{{%{family}%{style}}}" expands the sub-expression to construct the family name followed by the style, then takes the entire string and pads it on the left to be at least forty characters.

A *filter-out* tag is one starting with the character "-" followed by a comma-separated list of element names, followed by a sub-expression enclosed in curly braces. The sub-expression will be expanded but with a pattern that has the listed elements removed from it. For example, the format "%{-size,pixelsize{sub-expr}}" will expand "sub-expr" with *pattern* sans the size and pixelsize elements.

A *filter-in* tag is one starting with the character "+" followed by a comma-separated list of element names, followed by a sub-expression enclosed in curly braces. The sub-expression will be expanded but with a pattern that only has the listed elements from the surrounding pattern. For example, the format "%{+family,familylang{sub-expr}}" will expand "sub-expr" with a sub-pattern consisting only the family and family lang elements of *pattern*.

A *conditional* tag is one starting with the character "?" followed by a comma-separated list of element conditions, followed by two sub-expression enclosed in curly braces. An element condition can be an element name, in which case it tests whether the element is defined in pattern, or the character "!" followed by an element name, in which case the test is negated. The conditional passes if all the element conditions pass. The tag expands the first sub-expression if the conditional passes, and expands the second sub-expression otherwise. For example, the format "%{?size,dpi,!pixelsize{pass}{fail}}" will expand to "pass" if *pattern* has size and dpi elements but no pixelsize element, and to "fail" otherwise.

An *enumerate* tag is one starting with the string "[]" followed by a comma-separated list of element names, followed by a sub-expression enclosed in curly braces. The list of values for the named elements are walked in parallel and the sub-expression expanded each time with a pattern just having a single value for those elements, starting from the first value and continuing as long as any of those elements has a value. For example, the format "%{[]family,familylang{%{family} (%{familylang})\n}}" will expand the pattern "%{family} (%{familylang})\n" with a pattern having only the first value of the family and familylang elements, then expands it with the second values, then the third, etc.

As a special case, if an enumerate tag has only one element, and that element has only one value in the pattern, and that value is of type FcLangSet, the individual languages in the language set are enumerated.

A *builtin* tag is one starting with the character "=" followed by a builtin name. The following builtins are defined:

unparse

Expands to the result of calling FcNameUnparse() on the pattern.

fcmatch

Expands to the output of the default output format of the fc-match command on the pattern, without the final newline.

#### fc-list

Expands to the output of the default output format of the `fc-list` command on the *pattern*, without the final newline.

#### pkgkit

Expands to the list of PackageKit `font()` tags for the *pattern*. Currently this includes tags for each family name, and each language from the *pattern*, enumerated and sanitized into a set of tags terminated by newline. Package management systems can use these tags to tag their packages accordingly.

For example, the format `"%{+family,style{%{=unparse}}}\n"` will expand to an unparsed name containing only the family and style element values from *pattern*.

The contents of any tag can be followed by a set of zero or more *converters*. A converter is specified by the character `"|"` followed by the converter name and arguments. The following converters are defined:

#### basename

Replaces text with the results of calling `FcStrBasename()` on it.

#### dirname

Replaces text with the results of calling `FcStrDirname()` on it.

#### downcase

Replaces text with the results of calling `FcStrDowncase()` on it.

#### shescape

Escapes text for one level of shell expansion. (Escapes single-quotes, also encloses text in single-quotes.)

#### cescape

Escapes text such that it can be used as part of a C string literal. (Escapes backslash and double-quotes.)

#### xmlescape

Escapes text such that it can be used in XML and HTML. (Escapes less-than, greater-than, and ampersand.)

#### delete(*chars*)

Deletes all occurrences of each of the characters in *chars* from the text. **FIXME:** This converter is not UTF-8 aware yet.

#### escape(*chars*)

Escapes all occurrences of each of the characters in *chars* by prepending it by the first character in *chars*. **FIXME:** This converter is not UTF-8 aware yet.

#### translate(*from,to*)

Translates all occurrences of each of the characters in *from* by replacing them with their corresponding character in *to*. If *to* has fewer characters than *from*, it will be extended by repeating its last character. **FIXME:** This converter is not UTF-8 aware yet.

For example, the format `"%{family|downcase|delete( )}\n"` will expand to the values of the family element in *pattern*, lower-cased and with spaces removed.

## **Version**

Fontconfig version 2.6.99.behdad.20090508

## **FcFontSet**

An FcFontSet simply holds a list of patterns; these are used to return the results of listing available fonts.

## **FcFontSetCreate**

### **Name**

FcFontSetCreate — Create a font set

### **Synopsis**

```
#include <fontconfig.h>

FcFontSet * FcFontSetCreate(void);
```

### **Description**

Creates an empty font set.

### **Version**

Fontconfig version 2.6.99.behdad.20090508

## **FcFontSetDestroy**

### **Name**

FcFontSetDestroy — Destroy a font set

### **Synopsis**

```
#include <fontconfig.h>

void FcFontSetDestroy(FcFontSet *s);
```

## Description

Destroys a font set. Note that this destroys any referenced patterns as well.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcFontSetAdd

## Name

FcFontSetAdd — Add to a font set

## Synopsis

```
#include <fontconfig.h>

FcBool FcFontSetAdd(FcFontSet *s, FcPattern *font);
```

## Description

Adds a pattern to a font set. Note that the pattern is not copied before being inserted into the set. Returns FcFalse if the pattern cannot be inserted into the set (due to allocation failure). Otherwise returns FcTrue.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcFontSetList

## Name

FcFontSetList — List fonts from a set of font sets

## Synopsis

```
#include <fontconfig.h>

FcFontSet * FcFontSetList(FcConfig *config, FcFontSet **sets, int nsets,
FcPattern *pattern, FcObjectSet *object_set);
```

## Description

Selects fonts matching *pattern* from *sets*, creates patterns from those fonts containing only the objects in *object\_set* and returns the set of unique such patterns. If *config* is NULL, the default configuration is checked to be up to date, and used.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcFontSetMatch

### Name

FcFontSetMatch — Return the best font from a set of font sets

### Synopsis

```
#include <fontconfig.h>
```

```
FcPattern * FcFontSetMatch(FcConfig *config, FcFontSet **sets,  
intnsets, FcPattern *pattern, FcResult *result);
```

### Description

Finds the font in *sets* most closely matching *pattern* and returns the result of FcFontRenderPrepares for that font and the provided pattern. This function should be called only after FcConfigSubstitute and FcDefaultSubstitute have been called for *pattern*; otherwise the results will not be correct. If *config* is NULL, the current configuration is used. Returns NULL if an error occurs during this process.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcFontSetPrint

### Name

FcFontSetPrint — Print a set of patterns to stdout

## Synopsis

```
#include <fontconfig.h>

void FcFontSetPrint (FcFontSet *set);
```

## Description

This function is useful for diagnosing font related issues, printing the complete contents of every pattern in *set*. The format of the output is designed to be of help to users and developers, and may change at any time.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcFontSetSort

## Name

FcFontSetSort — Add to a font set

## Synopsis

```
#include <fontconfig.h>

FcFontSetSort (FcConfig *config, FcFontSet **sets, int nsets, FcPattern
*pattern, FcBool trim, FcCharSet **csp, FcResult *result);
```

## Description

Returns the list of fonts from *sets* sorted by closeness to *pattern*. If *trim* is FcTrue, elements in the list which don't include Unicode coverage not provided by earlier elements in the list are elided. The union of Unicode coverage of all of the fonts is returned in *csp*, if *csp* is not NULL. This function should be called only after FcConfigSubstitute and FcDefaultSubstitute have been called for *p*; otherwise the results will not be correct.

The returned FcFontSet references FcPattern structures which may be shared by the return value from multiple FcFontSort calls, applications cannot modify these patterns. Instead, they should be passed, along with *pattern* to FcFontRenderPrepare which combines them into a complete pattern.

The FcFontSet returned by FcFontSetSort is destroyed by calling FcFontSetDestroy.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcFontSetSortDestroy

### Name

FcFontSetSortDestroy — DEPRECATED destroy a font set

### Synopsis

```
#include <fontconfig.h>

FcFontSetSortDestroy(FcFontSet *set);
```

### Description

This function is DEPRECATED. FcFontSetSortDestroy destroys *set* by calling FcFontSetDestroy. Applications should use FcFontSetDestroy directly instead.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcObjectSet

An FcObjectSet holds a list of pattern property names; it is used to indicate which properties are to be returned in the patterns from FcFontList.

## FcObjectSetCreate

### Name

FcObjectSetCreate — Create an object set

### Synopsis

```
#include <fontconfig.h>

FcObjectSet * FcObjectSetCreate(void);
```

## **Description**

Creates an empty set.

## **Version**

Fontconfig version 2.6.99.behdad.20090508

# **FcObjectSetAdd**

## **Name**

FcObjectSetAdd — Add to an object set

## **Synopsis**

```
#include <fontconfig.h>

FcBool FcObjectSetAdd(FcObjectSet *os, const char *object);
```

## **Description**

Adds a property name to the set. Returns FcFalse if the property name cannot be inserted into the set (due to allocation failure). Otherwise returns FcTrue.

## **Version**

Fontconfig version 2.6.99.behdad.20090508

# **FcObjectSetDestroy**

## **Name**

FcObjectSetDestroy — Destroy an object set

## **Synopsis**

```
#include <fontconfig.h>

void FcObjectSetDestroy(FcObjectSet *os);
```



## Description

Destroys an object set.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcObjectSetBuild

## Name

FcObjectSetBuild, FcObjectSetVaBuild, FcObjectSetVapBuild —  
Build object set from args

## Synopsis

```
#include <fontconfig.h>

FcObjectSet * FcObjectSetBuild(const char *first, ...);
FcObjectSet * FcObjectSetVaBuild(const char *first, va_list va);
void FcObjectSetVapBuild(FcObjectSet *result, const char *first,
va_list va);
```

## Description

These build an object set from a null-terminated list of property names. FcObjectSetVapBuild is a macro version of FcObjectSetVaBuild which returns the result in the *result* variable directly.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FreeType specific functions

While the fontconfig library doesn't insist that FreeType be used as the rasterization mechanism for fonts, it does provide some convenience functions.

# FcFreeTypeCharIndex

## Name

FcFreeTypeCharIndex — map Unicode to glyph id

## Synopsis

```
#include <fontconfig.h>
#include <fcfreetype.h>

FT_UInt FcFreeTypeCharIndex(FT_Face face, FcChar32 ucs4);
```

## Description

Maps a Unicode char to a glyph index. This function uses information from several possible underlying encoding tables to work around broken fonts. As a result, this function isn't designed to be used in performance sensitive areas; results from this function are intended to be cached by higher level functions.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcFreeTypeCharSet

## Name

FcFreeTypeCharSet — compute unicode coverage

## Synopsis

```
#include <fontconfig.h>
#include <fcfreetype.h>

FcCharSet * FcFreeTypeCharSet(FT_Face face, FcBlanks *blanks);
```

## Description

Scans a FreeType face and returns the set of encoded Unicode chars. This scans several encoding tables to build as complete a list as possible. If 'blanks' is not 0, the glyphs in the font are examined and any blank glyphs not in 'blanks' are not placed in the returned FcCharSet.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcFreeTypeCharSetAndSpacing

### Name

FcFreeTypeCharSetAndSpacing — compute unicode coverage and spacing type

### Synopsis

```
#include <fontconfig.h>
#include <fcfreetype.h>

FcCharSet * FcFreeTypeCharSetAndSpacing (FT_Face face, FcBlanks *blanks,
int *spacing);
```

### Description

Scans a FreeType face and returns the set of encoded Unicode chars. This scans several encoding tables to build as complete a list as possible. If 'blanks' is not 0, the glyphs in the font are examined and any blank glyphs not in 'blanks' are not placed in the returned FcCharSet. *spacing* receives the computed spacing type of the font, one of FC\_MONO for a font where all glyphs have the same width, FC\_DUAL, where the font has glyphs in precisely two widths, one twice as wide as the other, or FC\_PROPORTIONAL where the font has glyphs of many widths.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcFreeTypeQuery

### Name

FcFreeTypeQuery — compute pattern from font file (and index)

### Synopsis

```
#include <fontconfig.h>
#include <fcfreetype.h>

FcPattern * FcFreeTypeQuery (const FcChar8 *file, int id, FcBlanks
*blanks, int *count);
```

## Description

Constructs a pattern representing the 'id'th font in 'file'. The number of fonts in 'file' is returned in 'count'.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcFreeTypeQueryFace

## Name

FcFreeTypeQueryFace — compute pattern from FT\_Face

## Synopsis

```
#include <fontconfig.h>
#include <fcfreetype.h>
```

```
FcPattern * FcFreeTypeQueryFace(const FT_Face face, const FcChar8
*file, int id, FcBlanks *blanks);
```

## Description

Constructs a pattern representing 'face'. 'file' and 'id' are used solely as data for pattern elements (FC\_FILE, FC\_INDEX and sometimes FC\_FAMILY).

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcValue

FcValue is a structure containing a type tag and a union of all possible datatypes. The tag is an enum of type *FcType* and is intended to provide a measure of run-time typechecking, although that depends on careful programming.

# FcValueDestroy

## Name

FcValueDestroy — Free a value

## Synopsis

```
#include <fontconfig.h>

void FcValueDestroy(FcValue v);
```

## Description

Frees any memory referenced by *v*. Values of type `FcTypeString`, `FcTypeMatrix` and `FcTypeCharSet` reference memory, the other types do not.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcValueSave

### Name

`FcValueSave` — Copy a value

## Synopsis

```
#include <fontconfig.h>

FcValue FcValueSave(FcValue v);
```

## Description

Returns a copy of *v* duplicating any object referenced by it so that *v* may be safely destroyed without harming the new value.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcValuePrint

### Name

`FcValuePrint` — Print a value to stdout

## Synopsis

```
#include <fontconfig.h>

void FcValuePrint (FcValue v);
```

## Description

Prints a human-readable representation of *v* to stdout. The format should not be considered part of the library specification as it may change in the future.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcValueEqual

## Name

FcValueEqual — Test two values for equality

## Synopsis

```
#include <fontconfig.h>

FcBool FcValueEqual (FcValue v_a, FcValue v_b);
```

## Description

Compares two values. Integers and Doubles are compared as numbers; otherwise the two values have to be the same type to be considered equal. Strings are compared ignoring case.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcCharSet

An FcCharSet is a boolean array indicating a set of unicode chars. Those associated with a font are marked constant and cannot be edited. FcCharSets may be reference counted internally to reduce memory consumption; this may be visible to applications as the result of FcCharSetCopy may return it's argument, and that CharSet may remain unmodifiable.

## FcCharSetCreate

### Name

FcCharSetCreate — Create an empty character set

### Synopsis

```
#include <fontconfig.h>

FcCharSet * FcCharSetCreate(void);
```

### Description

FcCharSetCreate allocates and initializes a new empty character set object.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcCharSetDestroy

### Name

FcCharSetDestroy — Destroy a character set

### Synopsis

```
#include <fontconfig.h>

void FcCharSetDestroy(FcCharSet *fcs);
```

## Description

`FcCharSetDestroy` decrements the reference count `fcs`. If the reference count becomes zero, all memory referenced is freed.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcCharSetAddChar

### Name

`FcCharSetAddChar` — Add a character to a charset

### Synopsis

```
#include <fontconfig.h>

FcBool FcCharSetAddChar(FcCharSet *fcs, FcChar32 ucs4);
```

### Description

`FcCharSetAddChar` adds a single unicode char to the set, returning `FcFalse` on failure, either as a result of a constant set or from running out of memory.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcCharSetCopy

### Name

`FcCharSetCopy` — Copy a charset

### Synopsis

```
#include <fontconfig.h>

FcCharSet * FcCharSetCopy(FcCharSet *src);
```



## Description

Makes a copy of *src*; note that this may not actually do anything more than increment the reference count on *src*.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcCharSetEqual

## Name

FcCharSetEqual — Compare two charsets

## Synopsis

```
#include <fontconfig.h>

FcBool FcCharSetEqual(const FcCharSet *a, const FcCharSet *b);
```

## Description

Returns whether *a* and *b* contain the same set of unicode chars.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcCharSetIntersect

## Name

FcCharSetIntersect — Intersect charsets

## Synopsis

```
#include <fontconfig.h>

FcCharSet * FcCharSetIntersect(const FcCharSet *a, const FcCharSet
*b);
```

## Description

Returns a set including only those chars found in both *a* and *b*.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcCharSetUnion

## Name

FcCharSetUnion — Add charsets

## Synopsis

```
#include <fontconfig.h>

FcCharSet * FcCharSetUnion(const FcCharSet *a, const FcCharSet *b);
```

## Description

Returns a set including only those chars found in either *a* or *b*.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcCharSetSubtract

## Name

FcCharSetSubtract — Subtract charsets

## Synopsis

```
#include <fontconfig.h>

FcCharSet * FcCharSetSubtract(const FcCharSet *a, const FcCharSet *b);
```

## Description

Returns a set including only those chars found in *a* but not *b*.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcCharSetMerge

## Name

FcCharSetMerge — Merge charsets

## Synopsis

```
#include <fontconfig.h>

FcBool FcCharSetMerge(FcCharSet *a, const FcCharSet *b, FcBool
*changed);
```

## Description

Adds all chars in *b* to *a*. In other words, this is an in-place version of FcCharSetUnion. If *changed* is not NULL, then it returns whether any new chars from *b* were added to *a*. Returns FcFalse on failure, either when *a* is a constant set or from running out of memory.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcCharSetHasChar

## Name

FcCharSetHasChar — Check a charset for a char

## Synopsis

```
#include <fontconfig.h>

FcBool FcCharSetHasChar(const FcCharSet *fcs, FcChar32 ucs4);
```

## Description

Returns whether *fcs* contains the char *ucs4*.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcCharSetCount

### Name

FcCharSetCount — Count entries in a charset

### Synopsis

```
#include <fontconfig.h>

FcChar32 FcCharSetCount(const FcCharSet *a);
```

### Description

Returns the total number of unicode chars in *a*.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcCharSetIntersectCount

### Name

FcCharSetIntersectCount — Intersect and count charsets

### Synopsis

```
#include <fontconfig.h>

FcChar32 FcCharSetIntersectCount(const FcCharSet *a, const FcCharSet
*b);
```

## Description

Returns the number of chars that are in both *a* and *b*.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcCharSetSubtractCount

## Name

FcCharSetSubtractCount — Subtract and count charsets

## Synopsis

```
#include <fontconfig.h>
```

```
FcChar32 FcCharSetSubtractCount(const FcCharSet *a, const FcCharSet *b);
```

## Description

Returns the number of chars that are in *a* but not in *b*.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcCharSetIsSubset

## Name

FcCharSetIsSubset — Test for charset inclusion

## Synopsis

```
#include <fontconfig.h>
```

```
FcBool FcCharSetIsSubset(const FcCharSet *a, const FcCharSet *b);
```

## Description

Returns whether *a* is a subset of *b*.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcCharSetFirstPage

### Name

FcCharSetFirstPage — Start enumerating charset contents

### Synopsis

```
#include <fontconfig.h>

FcChar32 FcCharSetFirstPage(const FcCharSet *a,
FcChar32[FC_CHARSET_MAP_SIZE] map, FcChar32 *next);
```

### Description

Builds an array of bits marking the first page of Unicode coverage of *a*. Returns the base of the array. *next* contains the next page in the font.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcCharSetNextPage

### Name

FcCharSetNextPage — Continue enumerating charset contents

## Synopsis

```
#include <fontconfig.h>

FcChar32 FcCharSetNextPage(const FcCharSet *a,
FcChar32[FC_CHARSET_MAP_SIZE] map, FcChar32 *next);
```

## Description

Builds an array of bits marking the Unicode coverage of *a* for page *\*next*. Returns the base of the array. *next* contains the next page in the font.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcCharSetCoverage

## Name

FcCharSetCoverage — DEPRECATED return coverage for a Unicode page

## Synopsis

```
#include <fontconfig.h>

FcChar32 FcCharSetCoverage(const FcCharSet *a, FcChar32 page,
FcChar32[8] result);
```

## Description

DEPRECATED This function returns a bitmask in *result* which indicates which code points in *page* are included in *a*. *FcCharSetCoverage* returns the next page in the charset which has any coverage.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcCharSetNew

### Name

FcCharSetNew — DEPRECATED alias for FcCharSetCreate

### Synopsis

```
#include <fontconfig.h>

FcCharSet * FcCharSetNew(void);
```

### Description

FcCharSetNew is a DEPRECATED alias for FcCharSetCreate.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcLangSet

An FcLangSet is a set of language names (each of which include language and an optional territory). They are used when selecting fonts to indicate which languages the fonts need to support. Each font is marked, using language orthography information built into fontconfig, with the set of supported languages.

## FcLangSetCreate

### Name

FcLangSetCreate — create a langset object

### Synopsis

```
#include <fontconfig.h>

FcLangSet * FcLangSetCreate(void);
```

### Description

FcLangSetCreate creates a new FcLangSet object.



## Version

Fontconfig version 2.6.99.behdad.20090508

# FcLangSetDestroy

## Name

FcLangSetDestroy — destroy a langset object

## Synopsis

```
#include <fontconfig.h>

void FcLangSetDestroy(FcLangSet *ls);
```

## Description

FcLangSetDestroy destroys a FcLangSet object, freeing all memory associated with it.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcLangSetCopy

## Name

FcLangSetCopy — copy a langset object

## Synopsis

```
#include <fontconfig.h>

FcLangSet * FcLangSetCopy(const FcLangSet *ls);
```

## Description

`FcLangSetCopy` creates a new `FcLangSet` object and populates it with the contents of *ls*.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcLangSetAdd

## Name

`FcLangSetAdd` — add a language to a langset

## Synopsis

```
#include <fontconfig.h>

FcBool FcLangSetAdd(FcLangSet *ls, const FcChar8 *lang);
```

## Description

*lang* is added to *ls*. *lang* should be of the form Ll-Tt where Ll is a two or three letter language from ISO 639 and Tt is a territory from ISO 3166.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcLangSetCompare

## Name

`FcLangSetCompare` — compare language sets

## Synopsis

```
#include <fontconfig.h>

FcLangResult FcLangSetCompare(const FcLangSet *ls_a, const FcLangSet
*ls_b);
```

## Description

`FcLangSetCompare` compares language coverage for `ls_a` and `ls_b`. If they share any language and territory pair, this function returns `FcLangEqual`. If they share a language but differ in which territory that language is for, this function returns `FcLangDiffentTerritory`. If they share no languages in common, this function returns `FcLangDifferentLang`.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcLangSetContains

### Name

`FcLangSetContains` — check langset subset relation

### Synopsis

```
#include <fontconfig.h>
```

```
FcBool FcLangSetContains(const FcLangSet *ls_a, const FcLangSet *ls_b);
```

### Description

`FcLangSetContains` returns `FcTrue` if `ls_a` contains every language in `ls_b`. `ls_a` will 'contain' a language from `ls_b` if `ls_a` has exactly the language, or either the language or `ls_a` has no territory.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcLangSetEqual

### Name

`FcLangSetEqual` — test for matching langsets

## Synopsis

```
#include <fontconfig.h>

FcBool FcLangSetEqual(const FcLangSet *ls_a, const FcLangSet *ls_b);
```

## Description

Returns FcTrue if and only if *ls\_a* supports precisely the same language and territory combinations as *ls\_b*.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcLangSetHash

## Name

FcLangSetHash — return a hash value for a langset

## Synopsis

```
#include <fontconfig.h>

FcChar32 FcLangSetHash(const FcLangSet *ls);
```

## Description

This function returns a value which depends solely on the languages supported by *ls*. Any language which equals *ls* will have the same result from FcLangSetHash. However, two langsets with the same hash value may not be equal.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcLangSetHasLang

### Name

FcLangSetHasLang — test langset for language support

### Synopsis

```
#include <fontconfig.h>

FcLangResult FcLangSetHasLang(const FcLangSet *ls, const FcChar8
*lang);
```

### Description

FcLangSetHasLang checks whether *ls* supports *lang*. If *ls* has a matching language and territory pair, this function returns FcLangEqual. If *ls* has a matching language but differs in which territory that language is for, this function returns FcLangDiffent-Territory. If *ls* has no matching language, this function returns FcLangDifferentLang.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcLangSetGetLangs

### Name

FcLangSetGetLangs — get the list of languages in the langset

### Synopsis

```
#include <fontconfig.h>

FcStrSet * FcLangSetGetLangs(const FcLangSet *ls);
```

### Description

Returns a string set of all languages in *langset*.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcGetLangs

### Name

FcGetLangs — Get list of languages

### Synopsis

```
#include <fontconfig.h>

FcStrSet * FcGetLangs(void);
```

### Description

Returns a string set of all known languages.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcLangGetCharSet

### Name

FcLangGetCharSet — Get character map for a language

### Synopsis

```
#include <fontconfig.h>

const FcCharSet * FcLangGetCharSet(const FcChar8 *lang);
```

### Description

Returns the FcCharMap for a language.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcMatrix

FcMatrix structures hold an affine transformation in matrix form.

## FcMatrixInit

### Name

FcMatrixInit — initialize an FcMatrix structure

### Synopsis

```
#include <fontconfig.h>

void FcMatrixInit (FcMatrix *matrix);
```

### Description

FcMatrixInit initializes *matrix* to the identity matrix.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcMatrixCopy

### Name

FcMatrixCopy — Copy a matrix

### Synopsis

```
#include <fontconfig.h>

void FcMatrixCopy (const FcMatrix *matrix);
```

## Description

`FcMatrixCopy` allocates a new `FcMatrix` and copies *mat* into it.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcMatrixEqual

## Name

`FcMatrixEqual` — Compare two matrices

## Synopsis

```
#include <fontconfig.h>

void FcMatrixEqual(const FcMatrix *matrix1, const FcMatrix *matrix2);
```

## Description

`FcMatrixEqual` compares *matrix1* and *matrix2* returning `FcTrue` when they are equal and `FcFalse` when they are not.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcMatrixMultiply

## Name

`FcMatrixMultiply` — Multiply matrices

## Synopsis

```
#include <fontconfig.h>

void FcMatrixMultiply(FcMatrix *result, const FcMatrix *matrix1, const
FcMatrix *matrix2);
```



## Description

`FcMatrixMultiply` multiplies *matrix1* and *matrix2* storing the result in *result*.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcMatrixRotate

### Name

`FcMatrixRotate` — Rotate a matrix

### Synopsis

```
#include <fontconfig.h>

void FcMatrixRotate(FcMatrix *matrix, double cos, double sin);
```

### Description

`FcMatrixRotate` rotates *matrix* by the angle whose sine is *sin* and cosine is *cos*. This is done by multiplying by the matrix:

```
cos  -sin
sin   cos
```

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcMatrixScale

### Name

`FcMatrixScale` — Scale a matrix

## Synopsis

```
#include <fontconfig.h>

void FcMatrixScale(FcMatrix *matrix, double sx, double dy);
```

## Description

`FcMatrixScale` multiplies *matrix* x values by *sx* and y values by *sy*. This is done by multiplying by the matrix:

$$\begin{pmatrix} sx & 0 \\ 0 & sy \end{pmatrix}$$

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcMatrixShear

### Name

`FcMatrixShear` — Shear a matrix

### Synopsis

```
#include <fontconfig.h>

void FcMatrixShear(FcMatrix *matrix, double sh, double sv);
```

### Description

`FcMatrixShare` shears *matrix* horizontally by *sh* and vertically by *sv*. This is done by multiplying by the matrix:

$$\begin{pmatrix} 1 & sh \\ sv & 1 \end{pmatrix}$$

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcConfig

An FcConfig object holds the internal representation of a configuration. There is a default configuration which applications may use by passing 0 to any function using the data within an FcConfig.

## FcConfigCreate

### Name

FcConfigCreate — Create a configuration

### Synopsis

```
#include <fontconfig.h>

FcConfig * FcConfigCreate(void);
```

### Description

Creates an empty configuration.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcConfigReference

### Name

FcConfigReference — Increment config reference count

### Synopsis

```
#include <fontconfig.h>

FcConfig * FcConfigReference(FcConfig *config);
```

## Description

Add another reference to *config*. Configs are freed only when the reference count reaches zero. If *config* is NULL, the current configuration is used. In that case this function will be similar to `FcConfigGetCurrent()` except that it increments the reference count before returning and the user is responsible for destroying the configuration when not needed anymore.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigDestroy

## Name

`FcConfigDestroy` — Destroy a configuration

## Synopsis

```
#include <fontconfig.h>

void FcConfigDestroy(FcConfig *config);
```

## Description

Decrements the config reference count. If all references are gone, destroys the configuration and any data associated with it. Note that calling this function with the return from `FcConfigGetCurrent` will cause a new configuration to be created for use as current configuration.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigSetCurrent

## Name

`FcConfigSetCurrent` — Set configuration as default

## Synopsis

```
#include <fontconfig.h>

FcBool FcConfigSetCurrent(FcConfig *config);
```

## Description

Sets the current default configuration to *config*. Implicitly calls `FcConfigBuildFonts` if necessary, returning `FcFalse` if that call fails.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcConfigGetCurrent

### Name

`FcConfigGetCurrent` — Return current configuration

### Synopsis

```
#include <fontconfig.h>

FcConfig * FcConfigGetCurrent(void);
```

### Description

Returns the current default configuration.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcConfigUptoDate

### Name

`FcConfigUptoDate` — Check timestamps on config files

## Synopsis

```
#include <fontconfig.h>

FcBool FcConfigUptoDate(FcConfig *config);
```

## Description

Checks all of the files related to *config* and returns whether any of them has been modified since the configuration was created. If *config* is NULL, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigHome

## Name

FcConfigHome — return the current home directory.

## Synopsis

```
#include <fontconfig.h>

FcChar8 * FcConfigHome(void);
```

## Description

Return the current user's home directory, if it is available, and if using it is enabled, and NULL otherwise. See also FcConfigEnableHome).

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcConfigEnableHome

### Name

FcConfigEnableHome — controls use of the home directory.

### Synopsis

```
#include <fontconfig.h>

FcBool FcConfigEnableHome(FcBool enable);
```

### Description

If *enable* is FcTrue, then Fontconfig will use various files which are specified relative to the user's home directory (using the ~ notation in the configuration). When *enable* is FcFalse, then all use of the home directory in these contexts will be disabled. The previous setting of the value is returned.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcConfigBuildFonts

### Name

FcConfigBuildFonts — Build font database

### Synopsis

```
#include <fontconfig.h>

FcBool FcConfigBuildFonts(FcConfig *config);
```

### Description

Builds the set of available fonts for the given configuration. Note that any changes to the configuration after this call have indeterminate effects. Returns FcFalse if this operation runs out of memory. If *config* is NULL, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigGetConfigDirs

## Name

FcConfigGetConfigDirs — Get config directories

## Synopsis

```
#include <fontconfig.h>

FcStrList * FcConfigGetConfigDirs(FcConfig *config);
```

## Description

Returns the list of font directories specified in the configuration files for *config*. Does not include any subdirectories. If *config* is NULL, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigGetFontDirs

## Name

FcConfigGetFontDirs — Get font directories

## Synopsis

```
#include <fontconfig.h>

FcStrList * FcConfigGetFontDirs(FcConfig *config);
```



## Description

Returns the list of font directories in *config*. This includes the configured font directories along with any directories below those in the filesystem. If *config* is NULL, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigGetConfigFiles

## Name

FcConfigGetConfigFiles — Get config files

## Synopsis

```
#include <fontconfig.h>

FcStrList * FcConfigGetConfigFiles(FcConfig *config);
```

## Description

Returns the list of known configuration files used to generate *config*. If *config* is NULL, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigGetCache

## Name

FcConfigGetCache — DEPRECATED used to return per-user cache filename

## Synopsis

```
#include <fontconfig.h>

FcChar8 * FcConfigGetCache(FcConfig *config);
```

## Description

With fontconfig no longer using per-user cache files, this function now simply returns NULL to indicate that no per-user file exists.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigGetCacheDirs

## Name

FcConfigGetCacheDirs — return the list of directories searched for cache files

## Synopsis

```
#include <fontconfig.h>

FcStrList * FcConfigGetCacheDirs(FcConfig *config);
```

## Description

FcConfigGetCacheDirs returns a string list containing all of the directories that fontconfig will search when attempting to load a cache file for a font directory. If *config* is NULL, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigGetFonts

## Name

FcConfigGetFonts — Get config font set

## Synopsis

```
#include <fontconfig.h>

FcFontSet * FcConfigGetFonts(FcConfig *config, FcSetName set);
```

## Description

Returns one of the two sets of fonts from the configuration as specified by *set*. This font set is owned by the library and must not be modified or freed. If *config* is NULL, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigGetBlanks

## Name

FcConfigGetBlanks — Get config blanks

## Synopsis

```
#include <fontconfig.h>

FcBlanks * FcConfigGetBlanks(FcConfig *config);
```

## Description

Returns the FcBlanks object associated with the given configuration, if no blanks were present in the configuration, this function will return 0. The returned FcBlanks object if not NULL, is valid as long as the owning FcConfig is alive. If *config* is NULL, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcConfigGetRescanInterval

### Name

FcConfigGetRescanInterval — Get config rescan interval

### Synopsis

```
#include <fontconfig.h>

int FcConfigGetRescanInterval(FcConfig *config);
```

### Description

Returns the interval between automatic checks of the configuration (in seconds) specified in *config*. The configuration is checked during a call to FcFontList when this interval has passed since the last check. An interval setting of zero disables automatic checks. If *config* is NULL, the current configuration is used.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcConfigSetRescanInterval

### Name

FcConfigSetRescanInterval — Set config rescan interval

### Synopsis

```
#include <fontconfig.h>

FcBool FcConfigSetRescanInterval(FcConfig *config, int rescanInterval);
```

### Description

Sets the rescan interval. Returns FcFalse if the interval cannot be set (due to allocation failure). Otherwise returns FcTrue. An interval setting of zero disables automatic checks. If *config* is NULL, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigAppFontAddFile

## Name

FcConfigAppFontAddFile — Add font file to font database

## Synopsis

```
#include <fontconfig.h>

FcBool FcConfigAppFontAddFile(FcConfig *config, const FcChar8 *file);
```

## Description

Adds an application-specific font to the configuration. Returns FcFalse if the fonts cannot be added (due to allocation failure). Otherwise returns FcTrue. If *config* is NULL, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigAppFontAddDir

## Name

FcConfigAppFontAddDir — Add fonts from directory to font database

## Synopsis

```
#include <fontconfig.h>

FcBool FcConfigAppFontAddDir(FcConfig *config, const FcChar8 *dir);
```

## Description

Scans the specified directory for fonts, adding each one found to the application-specific set of fonts. Returns `FcFalse` if the fonts cannot be added (due to allocation failure). Otherwise returns `FcTrue`. If *config* is `NULL`, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigAppFontClear

## Name

`FcConfigAppFontClear` — Remove all app fonts from font database

## Synopsis

```
#include <fontconfig.h>

void FcConfigAppFontClear (FcConfig *config);
```

## Description

Clears the set of application-specific fonts. If *config* is `NULL`, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigSubstituteWithPat

## Name

`FcConfigSubstituteWithPat` — Execute substitutions

## Synopsis

```
#include <fontconfig.h>
```

```
FcBool FcConfigSubstituteWithPat(FcConfig *config, FcPattern *p,  
FcPattern *p_pat, FcMatchKind kind);
```

## Description

Performs the sequence of pattern modification operations, if *kind* is `FcMatchPattern`, then those tagged as pattern operations are applied, else if *kind* is `FcMatchFont`, those tagged as font operations are applied and *p\_pat* is used for <test> elements with target=pattern. Returns `FcFalse` if the substitution cannot be performed (due to allocation failure). Otherwise returns `FcTrue`. If *config* is `NULL`, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigSubstitute

## Name

FcConfigSubstitute — Execute substitutions

## Synopsis

```
#include <fontconfig.h>
```

```
FcBool FcConfigSubstitute(FcConfig *config, FcPattern *p, FcMatchKind  
kind);
```

## Description

Calls `FcConfigSubstituteWithPat` setting *p\_pat* to `NULL`. Returns `FcFalse` if the substitution cannot be performed (due to allocation failure). Otherwise returns `FcTrue`. If *config* is `NULL`, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcFontMatch

### Name

FcFontMatch — Return best font

### Synopsis

```
#include <fontconfig.h>

FcPattern * FcFontMatch(FcConfig *config, FcPattern *p, FcResult
*result);
```

### Description

Finds the font in *sets* most closely matching *pattern* and returns the result of FcFontRenderPrepare for that font and the provided pattern. This function should be called only after FcConfigSubstitute and FcDefaultSubstitute have been called for *p*; otherwise the results will not be correct. If *config* is NULL, the current configuration is used.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcFontSort

### Name

FcFontSort — Return list of matching fonts

### Synopsis

```
#include <fontconfig.h>

FcFontSet * FcFontSort(FcConfig *config, FcPattern *p, FcBool trim,
FcCharSet **csp, FcResult *result);
```

### Description

Returns the list of fonts sorted by closeness to *p*. If *trim* is FcTrue, elements in the list which don't include Unicode coverage not provided by earlier elements in the list are elided. The union of Unicode coverage of all of the fonts is returned in *csp*, if *csp* is not NULL. This function should be called only after FcConfigSubstitute and FcDefaultSubstitute have been called for *p*; otherwise the results will not be correct.



The returned `FcFontSet` references `FcPattern` structures which may be shared by the return value from multiple `FcFontSort` calls, applications must not modify these patterns. Instead, they should be passed, along with *p* to `FcFontRenderPrepare` which combines them into a complete pattern.

The `FcFontSet` returned by `FcFontSort` is destroyed by calling `FcFontSetDestroy`. If *config* is `NULL`, the current configuration is used.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcFontRenderPrepare

## Name

`FcFontRenderPrepare` — Prepare pattern for loading font file

## Synopsis

```
#include <fontconfig.h>
```

```
FcPattern * FcFontRenderPrepare(FcConfig *config, FcPattern *pat,  
FcPattern *font);
```

## Description

Creates a new pattern consisting of elements of *font* not appearing in *pat*, elements of *pat* not appearing in *font* and the best matching value from *pat* for elements appearing in both. The result is passed to `FcConfigSubstituteWithPat` with *kind* `FcMatchFont` and then returned.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcFontList

## Name

`FcFontList` — List fonts

## Synopsis

```
#include <fontconfig.h>

FcFontSet * FcFontList (FcConfig *config, FcPattern *p, FcObjectSet
*os);
```

## Description

Selects fonts matching *p*, creates patterns from those fonts containing only the objects in *os* and returns the set of unique such patterns. If *config* is NULL, the default configuration is checked to be up to date, and used.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcConfigFilename

### Name

FcConfigFilename — Find a config file

## Synopsis

```
#include <fontconfig.h>

FcChar8 * FcConfigFilename (const FcChar8 *name);
```

## Description

Given the specified external entity name, return the associated filename. This provides applications a way to convert various configuration file references into filename form.

A null or empty *name* indicates that the default configuration file should be used; which file this references can be overridden with the FC\_CONFIG\_FILE environment variable. Next, if the name starts with ~, it refers to a file in the current users home directory. Otherwise if the name doesn't start with '/', it refers to a file in the default configuration directory; the built-in default directory can be overridden with the FC\_CONFIG\_DIR environment variable.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcConfigParseAndLoad

## Name

FcConfigParseAndLoad — load a configuration file

## Synopsis

```
#include <fontconfig.h>
```

```
FcBool FcConfigParseAndLoad(FcConfig *config, const FcChar8 *file,  
FcBool complain);
```

## Description

Walks the configuration in 'file' and constructs the internal representation in 'config'. Any include files referenced from within 'file' will be loaded and parsed. If 'complain' is FcFalse, no warning will be displayed if 'file' does not exist. Error and warning messages will be output to stderr. Returns FcFalse if some error occurred while loading the file, either a parse error, semantic error or allocation failure. Otherwise returns FcTrue.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcObjectType

Provides for application-specified font name object types so that new pattern elements can be generated from font names.

# FcNameRegisterObjectTypes

## Name

FcNameRegisterObjectTypes — Register object types

## Synopsis

```
#include <fontconfig.h>

FcBool FcNameRegisterObjectTypes(const FcObjectType *types, int ntype);
```

## Description

Register *ntype* new object types. Returns FcFalse if some of the names cannot be registered (due to allocation failure). Otherwise returns FcTrue.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcNameUnregisterObjectTypes

## Name

FcNameUnregisterObjectTypes — Unregister object types

## Synopsis

```
#include <fontconfig.h>

FcBool FcNameUnregisterObjectTypes(const FcObjectType *types, int
ntype);
```

## Description

Unregister *ntype* object types. Returns FcTrue.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcNameGetObjectType

## Name

FcNameGetObjectType — Lookup an object type

## Synopsis

```
#include <fontconfig.h>

const FcObjectType * FcNameGetObjectType(const char *object);
```

## Description

Return the object type for the pattern element named *object*.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcConstant

Provides for application-specified symbolic constants for font names.

## FcNameRegisterConstants

### Name

FcNameRegisterConstants — Register symbolic constants

## Synopsis

```
#include <fontconfig.h>

FcBool FcNameRegisterConstants(const FcConstant *consts, int nconsts);
```

## Description

Register *nconsts* new symbolic constants. Returns FcFalse if the constants cannot be registered (due to allocation failure). Otherwise returns FcTrue.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcNameUnregisterConstants

### Name

FcNameUnregisterConstants — Unregister symbolic constants

### Synopsis

```
#include <fontconfig.h>

FcBool FcNameUnregisterConstants(const FcConstant *consts, int nconsts);
```

### Description

Unregister *nconsts* symbolic constants. Returns FcFalse if the specified constants were not registered. Otherwise returns FcTrue.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcNameGetConstant

### Name

FcNameGetConstant — Lookup symbolic constant

### Synopsis

```
#include <fontconfig.h>

const FcConstant * FcNameGetConstant(FcChar8 *string);
```

### Description

Return the FcConstant structure related to symbolic constant *string*.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcNameConstant

### Name

FcNameConstant — Get the value for a symbolic constant

### Synopsis

```
#include <fontconfig.h>

FcBool FcNameConstant(FcChar8 *string, int *result);
```

### Description

Returns whether a symbolic constant with name *string* is registered, placing the value of the constant in *result* if present.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcBlanks

An FcBlanks object holds a list of Unicode chars which are expected to be blank when drawn. When scanning new fonts, any glyphs which are empty and not in this list will be assumed to be broken and not placed in the FcCharSet associated with the font. This provides a significantly more accurate CharSet for applications.

## FcBlanksCreate

### Name

FcBlanksCreate — Create an FcBlanks

### Synopsis

```
#include <fontconfig.h>

FcBlanks * FcBlanksCreate(void);
```

## **Description**

Creates an empty FcBlanks object.

## **Version**

Fontconfig version 2.6.99.behdad.20090508

# **FcBlanksDestroy**

## **Name**

FcBlanksDestroy — Destroy and FcBlanks

## **Synopsis**

```
#include <fontconfig.h>

void FcBlanksDestroy(FcBlanks *b);
```

## **Description**

Destroys an FcBlanks object, freeing any associated memory.

## **Version**

Fontconfig version 2.6.99.behdad.20090508

# **FcBlanksAdd**

## **Name**

FcBlanksAdd — Add a character to an FcBlanks

## **Synopsis**

```
#include <fontconfig.h>

FcBool FcBlanksAdd(FcBlanks *b, FcChar32 ucs4);
```



## Description

Adds a single character to an FcBlanks object, returning FcFalse if this process ran out of memory.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcBlanksIsMember

### Name

FcBlanksIsMember — Query membership in an FcBlanks

### Synopsis

```
#include <fontconfig.h>

FcBool FcBlanksIsMember(FcBlanks *b, FcChar32 ucs4);
```

### Description

Returns whether the specified FcBlanks object contains the indicated Unicode value.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcAtomic

These functions provide a safe way to update config files, allowing ongoing reading of the old config file while locked for writing and ensuring that a consistent and complete version of the config file is always available.

## FcAtomicCreate

### Name

FcAtomicCreate — create an FcAtomic object

## Synopsis

```
#include <fontconfig.h>

FcAtomic * FcAtomicCreate(const FcChar8 *file);
```

## Description

Creates a data structure containing data needed to control access to *file*. Writing is done to a separate file. Once that file is complete, the original configuration file is atomically replaced so that reading process always see a consistent and complete file without the need to lock for reading.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcAtomicLock

### Name

FcAtomicLock — lock a file

## Synopsis

```
#include <fontconfig.h>

FcBool FcAtomicLock(FcAtomic *atomic);
```

## Description

Attempts to lock the file referenced by *atomic*. Returns FcFalse if the file is already locked, else returns FcTrue and leaves the file locked.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcAtomicNewFile

### Name

FcAtomicNewFile — return new temporary file name

### Synopsis

```
#include <fontconfig.h>

FcChar8 * FcAtomicNewFile(FcAtomic *atomic);
```

### Description

Returns the filename for writing a new version of the file referenced by *atomic*.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcAtomicOrigFile

### Name

FcAtomicOrigFile — return original file name

### Synopsis

```
#include <fontconfig.h>

FcChar8 * FcAtomicOrigFile(FcAtomic *atomic);
```

### Description

Returns the file referenced by *atomic*.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcAtomicReplaceOrig

### Name

FcAtomicReplaceOrig — replace original with new

### Synopsis

```
#include <fontconfig.h>

FcBool FcAtomicReplaceOrig(FcAtomic *atomic);
```

### Description

Replaces the original file referenced by *atomic* with the new file. Returns FcFalse if the file cannot be replaced due to permission issues in the filesystem. Otherwise returns FcTrue.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcAtomicDeleteNew

### Name

FcAtomicDeleteNew — delete new file

### Synopsis

```
#include <fontconfig.h>

void FcAtomicDeleteNew(FcAtomic *atomic);
```

### Description

Deletes the new file. Used in error recovery to back out changes.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcAtomicUnlock

## Name

FcAtomicUnlock — unlock a file

## Synopsis

```
#include <fontconfig.h>

void FcAtomicUnlock(FcAtomic *atomic);
```

## Description

Unlocks the file.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcAtomicDestroy

## Name

FcAtomicDestroy — destroy an FcAtomic object

## Synopsis

```
#include <fontconfig.h>

void FcAtomicDestroy(FcAtomic *atomic);
```

## Description

Destroys *atomic*.

## Version

Fontconfig version 2.6.99.behdad.20090508

## File and Directory routines

These routines work with font files and directories, including font directory cache files.

## FcFileScan

### Name

FcFileScan — scan a font file

### Synopsis

```
#include <fontconfig.h>
```

```
FcBool FcFileScan(FcFontSet *set, FcStrSet *dirs, FcFileCache *cache,  
FcBlanks *blanks, const FcChar8 *file, FcBool force);
```

### Description

Scans a single file and adds all fonts found to *set*. If *force* is `FcTrue`, then the file is scanned even if associated information is found in *cache*. If *file* is a directory, it is added to *dirs*. Whether fonts are found depends on fontconfig policy as well as the current configuration. Internally, fontconfig will ignore BDF and PCF fonts which are not in Unicode (or the effectively equivalent ISO Latin-1) encoding as those are not usable by Unicode-based applications. The configuration can ignore fonts based on filename or contents of the font file itself. Returns `FcFalse` if any of the fonts cannot be added (due to allocation failure). Otherwise returns `FcTrue`.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcFileIsDir

### Name

FcFileIsDir — check whether a file is a directory

## Synopsis

```
#include <fontconfig.h>

FcBool FcFileIsDir(const FcChar8 *file);
```

## Description

Returns `FcTrue` if *file* is a directory, otherwise returns `FcFalse`.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcDirScan

## Name

`FcDirScan` — scan a font directory without caching it

## Synopsis

```
#include <fontconfig.h>

FcBool FcDirScan(FcFontSet *set, FcStrSet *dirs, FcFileCache *cache,
FcBlanks *blanks, const FcChar8 *dir, FcBool force);
```

## Description

If *cache* is not zero or if *force* is `FcFalse`, this function currently returns `FcFalse`. Otherwise, it scans an entire directory and adds all fonts found to *set*. Any subdirectories found are added to *dirs*. Calling this function does not create any cache files. Use `FcDirCacheRead()` if caching is desired.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcDirSave

### Name

FcDirSave — DEPRECATED: formerly used to save a directory cache

### Synopsis

```
#include <fontconfig.h>

FcBool FcDirSave(FcFontSet *set, FcStrSet *dirs, const FcChar8 *dir);
```

### Description

This function now does nothing aside from returning FcFalse. It used to create the per-directory cache file for *dir* and populate it with the fonts in *set* and subdirectories in *dirs*. All of this functionality is now automatically managed by FcDirCacheLoad and FcDirCacheRead.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcDirCacheUnlink

### Name

FcDirCacheUnlink — Remove all caches related to *dir*

### Synopsis

```
#include <fontconfig.h>

FcBool FcDirCacheUnlink(const FcChar8 *dir, FcConfig *config);
```

### Description

Scans the cache directories in *config*, removing any instances of the cache file for *dir*. Returns FcFalse when some internal error occurs (out of memory, etc). Errors actually unlinking any files are ignored.



## Version

Fontconfig version 2.6.99.behdad.20090508

# FcDirCacheValid

## Name

FcDirCacheValid — check directory cache

## Synopsis

```
#include <fontconfig.h>

FcBool FcDirCacheValid(const FcChar8 *dir);
```

## Description

Returns FcTrue if *dir* has an associated valid cache file, else returns FcFalse

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcDirCacheLoad

## Name

FcDirCacheLoad — load a directory cache

## Synopsis

```
#include <fontconfig.h>

FcCache * FcDirCacheLoad(const FcChar8 *dir, FcConfig *config, FcChar8
**cache_file);
```

## Description

Loads the cache related to *dir*. If no cache file exists, returns NULL. The name of the cache file is returned in *cache\_file*, unless that is NULL. See also FcDirCacheRead.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcDirCacheRead

### Name

FcDirCacheRead — read or construct a directory cache

### Synopsis

```
#include <fontconfig.h>

FcCache * FcDirCacheRead(const FcChar8 *dir, FcBool force, FcConfig
*config);
```

### Description

This returns a cache for *dir*. If *force* is FcFalse, then an existing, valid cache file will be used. Otherwise, a new cache will be created by scanning the directory and that returned.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcDirCacheLoadFile

### Name

FcDirCacheLoadFile — load a cache file

### Synopsis

```
#include <fontconfig.h>
```

```
FcCache * FcDirCacheLoadFile(const FcChar8 *cache_file, struct stat
*file_stat);
```

## Description

This function loads a directory cache from *cache\_file*. If *file\_stat* is non-NULL, it will be filled with the results of `stat(2)` on the cache file.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcDirCacheUnload

### Name

FcDirCacheUnload — unload a cache file

### Synopsis

```
#include <fontconfig.h>

void FcDirCacheUnload(FcCache *cache);
```

## Description

This function dereferences *cache*. When no other references to it remain, all memory associated with the cache will be freed.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcCache routines

These routines work with font directory caches, accessing their contents in limited ways. It is not expected that normal applications will need to use these functions.

## FcCacheDir

### Name

FcCacheDir — Return directory of *cache*

### Synopsis

```
#include <fontconfig.h>

const FcChar8 * FcCacheDir(const FcCache *cache);
```

### Description

This function returns the directory from which the cache was constructed.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcCacheCopySet

### Name

FcCacheCopySet — Returns a copy of the fontset from *cache*

### Synopsis

```
#include <fontconfig.h>

FcFontSet * FcCacheCopySet(const FcCache *cache);
```

### Description

The returned fontset contains each of the font patterns from *cache*. This fontset may be modified, but the patterns from the cache are read-only.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcCacheSubdir

### Name

`FcCacheSubdir` — Return the *i*'th subdirectory.

### Synopsis

```
#include <fontconfig.h>

const FcChar8 * FcCacheSubdir(const FcCache *cache, inti);
```

### Description

The set of subdirectories stored in a cache file are indexed by this function, *i* should range from 0 to *n*-1, where *n* is the return value from `FcCacheNumSubdir`.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcCacheNumSubdir

### Name

`FcCacheNumSubdir` — Return the number of subdirectories in *cache*.

### Synopsis

```
#include <fontconfig.h>

int FcCacheNumSubdir(const FcCache *cache);
```

### Description

This returns the total number of subdirectories in the cache.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcCacheNumFont

### Name

`FcCacheNumFont` — Returns the number of fonts in *cache*.

### Synopsis

```
#include <fontconfig.h>

int FcCacheNumFont(const FcCache *cache);
```

### Description

This returns the number of fonts which would be included in the return from `FcCacheCopySet`.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrSet and FcStrList

A data structure for enumerating strings, used to list directories while scanning the configuration as directories are added while scanning.

## FcStrSetCreate

### Name

`FcStrSetCreate` — create a string set

### Synopsis

```
#include <fontconfig.h>

FcStrSet * FcStrSetCreate(void);
```

### Description

Create an empty set.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrSetMember

### Name

`FcStrSetMember` — check set for membership

### Synopsis

```
#include <fontconfig.h>

FcBool FcStrSetMember(FcStrSet *set, const FcChar8 *s);
```

### Description

Returns whether *s* is a member of *set*.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrSetEqual

### Name

`FcStrSetEqual` — check sets for equality

### Synopsis

```
#include <fontconfig.h>

FcBool FcStrSetEqual(FcStrSet *set_a, FcStrSet *set_b);
```

### Description

Returns whether *set\_a* contains precisely the same strings as *set\_b*. Ordering of strings within the two sets is not considered.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrSetAdd

### Name

FcStrSetAdd — add to a string set

### Synopsis

```
#include <fontconfig.h>

FcBool FcStrSetAdd(FcStrSet *set, const FcChar8 *s);
```

### Description

Adds a copy of *s* to *set*.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrSetAddFilename

### Name

FcStrSetAddFilename — add a filename to a string set

### Synopsis

```
#include <fontconfig.h>

FcBool FcStrSetAddFilename(FcStrSet *set, const FcChar8 *s);
```

### Description

Adds a copy *s* to *set*, The copy is created with FcStrCopyFilename so that leading '~' values are replaced with the value of the HOME environment variable.



## Version

Fontconfig version 2.6.99.behdad.20090508

# FcStrSetDel

## Name

FcStrSetDel — delete from a string set

## Synopsis

```
#include <fontconfig.h>

FcBool FcStrSetDel(FcStrSet *set, const FcChar8 *s);
```

## Description

Removes *s* from *set*, returning FcTrue if *s* was a member else FcFalse.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcStrSetDestroy

## Name

FcStrSetDestroy — destroy a string set

## Synopsis

```
#include <fontconfig.h>

void FcStrSetDestroy(FcStrSet *set);
```

## Description

Destroys *set*.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrListCreate

### Name

FcStrListCreate — create a string iterator

### Synopsis

```
#include <fontconfig.h>

FcStrList * FcStrListCreate(FcStrSet *set);
```

### Description

Creates an iterator to list the strings in *set*.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrListNext

### Name

FcStrListNext — get next string in iteration

### Synopsis

```
#include <fontconfig.h>

FcChar8 * FcStrListNext(FcStrList *list);
```

### Description

Returns the next string in *set*.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrListDone

### Name

FcStrListDone — destroy a string iterator

### Synopsis

```
#include <fontconfig.h>

void FcStrListDone(FcStrList *list);
```

### Description

Destroys the enumerator *list*.

### Version

Fontconfig version 2.6.99.behdad.20090508

## String utilities

Fontconfig manipulates many UTF-8 strings represented with the FcChar8 type. These functions are exposed to help applications deal with these UTF-8 strings in a locale-insensitive manner.

## FcUtf8ToUcs4

### Name

FcUtf8ToUcs4 — convert UTF-8 to UCS4

### Synopsis

```
#include <fontconfig.h>

int FcUtf8ToUcs4(FcChar8 *src, FcChar32 *dst, int len);
```

## Description

Converts the next Unicode char from *src* into *dst* and returns the number of bytes containing the char. *src* must be at least *len* bytes long.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcUcs4ToUtf8

### Name

FcUcs4ToUtf8 — convert UCS4 to UTF-8

### Synopsis

```
#include <fontconfig.h>

int FcUcs4ToUtf8(FcChar32 src, FcChar8 dst[FC_UTF8_MAX_LEN]);
```

### Description

Converts the Unicode char from *src* into *dst* and returns the number of bytes needed to encode the char.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcUtf8Len

### Name

FcUtf8Len — count UTF-8 encoded chars

### Synopsis

```
#include <fontconfig.h>

FcBool FcUtf8Len(FcChar8 *src, int len, int *nchar, int *wchar);
```

## Description

Counts the number of Unicode chars in *len* bytes of *src*. Places that count in *nchar*. *wchar* contains 1, 2 or 4 depending on the number of bytes needed to hold the largest unicode char counted. The return value indicates whether *src* is a well-formed UTF8 string.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcUtf16ToUcs4

### Name

FcUtf16ToUcs4 — convert UTF-16 to UCS4

### Synopsis

```
#include <fontconfig.h>

int FcUtf16ToUcs4(FcChar8 *src, FcEndian endian, FcChar32 *dst, int
len);
```

### Description

Converts the next Unicode char from *src* into *dst* and returns the number of bytes containing the char. *src* must be at least *len* bytes long. Bytes of *src* are combined into 16-bit units according to *endian*.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcUtf16Len

### Name

FcUtf16Len — count UTF-16 encoded chars

## Synopsis

```
#include <fontconfig.h>

FcBool FcUtf16Len(FcChar8 *src, FcEndian endian, int len, int *nchar,
int *wchar);
```

## Description

Counts the number of Unicode chars in *len* bytes of *src*. Bytes of *src* are combined into 16-bit units according to *endian*. Places that count in *nchar*. *wchar* contains 1, 2 or 4 depending on the number of bytes needed to hold the largest unicode char counted. The return value indicates whether *string* is a well-formed UTF16 string.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcIsLower

### Name

`FcIsLower` — check for lower case ASCII character

## Synopsis

```
#include <fontconfig.h>

FcBool FcIsLower(FcChar8c);
```

## Description

This macro checks whether *c* is an lower case ASCII letter.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcIsUpper

### Name

FcIsUpper — check for upper case ASCII character

### Synopsis

```
#include <fontconfig.h>

FcBool FcIsUpper(FcChar8c);
```

### Description

This macro checks whether *c* is a upper case ASCII letter.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcToLower

### Name

FcToLower — convert upper case ASCII to lower case

### Synopsis

```
#include <fontconfig.h>

FcChar8 FcToLower(FcChar8c);
```

### Description

This macro converts upper case ASCII *c* to the equivalent lower case letter.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrCopy

### Name

FcStrCopy — duplicate a string

### Synopsis

```
#include <fontconfig.h>

FcChar8 * FcStrCopy(const FcChar8 *s);
```

### Description

Allocates memory, copies *s* and returns the resulting buffer. Yes, this is `strdup`, but that function isn't available on every platform.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrDowncase

### Name

FcStrDowncase — create a lower case translation of a string

### Synopsis

```
#include <fontconfig.h>

FcChar8 * FcStrDowncase(const FcChar8 *s);
```

### Description

Allocates memory, copies *s*, converting upper case letters to lower case and returns the allocated buffer.



## Version

Fontconfig version 2.6.99.behdad.20090508

# FcStrCopyFilename

## Name

FcStrCopyFilename — create a complete path from a filename

## Synopsis

```
#include <fontconfig.h>

FcChar8 * FcStrCopyFilename(const FcChar8 *s);
```

## Description

FcStrCopyFilename constructs an absolute pathname from *s*. It converts any leading '~' characters in to the value of the HOME environment variable, and any relative paths are converted to absolute paths using the current working directory. Sequences of '/' characters are converted to a single '/', and names containing the current directory '.' or parent directory '..' are correctly reconstructed. Returns NULL if '~' is the leading character and HOME is unset or disabled (see FcConfigEnableHome).

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcStrCmp

## Name

FcStrCmp — compare UTF-8 strings

## Synopsis

```
#include <fontconfig.h>

int FcStrCmp(const FcChar8 *s1, const FcChar8 *s2);
```

## Description

Returns the usual  $<0, 0, >0$  result of comparing  $s1$  and  $s2$ .

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcStrCmpIgnoreCase

## Name

FcStrCmpIgnoreCase — compare UTF-8 strings ignoring case

## Synopsis

```
#include <fontconfig.h>

int FcStrCmpIgnoreCase(const FcChar8 *s1, const FcChar8 *s2);
```

## Description

Returns the usual  $<0, 0, >0$  result of comparing  $s1$  and  $s2$ . This test is case-insensitive for all proper UTF-8 encoded strings.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcStrStr

## Name

FcStrStr — locate UTF-8 substring

## Synopsis

```
#include <fontconfig.h>

FcChar8 * FcStrStr(const FcChar8 *s1, const FcChar8 *s2);
```

## Description

Returns the location of *s2* in *s1*. Returns NULL if *s2* is not present in *s1*. This test will operate properly with UTF8 encoded strings.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcStrStrIgnoreCase

## Name

FcStrStrIgnoreCase — locate UTF-8 substring ignoring ASCII case

## Synopsis

```
#include <fontconfig.h>

FcChar8 * FcStrStrIgnoreCase(const FcChar8 *s1, const FcChar8 *s2);
```

## Description

Returns the location of *s2* in *s1*, ignoring case. Returns NULL if *s2* is not present in *s1*. This test is case-insensitive for all proper UTF-8 encoded strings.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcStrPlus

## Name

FcStrPlus — concatenate two strings

## Synopsis

```
#include <fontconfig.h>

FcChar8 * FcStrPlus(const FcChar8 *s1, const FcChar8 *s2);
```

## Description

This function allocates new storage and places the concatenation of *s1* and *s2* there, returning the new string.

## Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrFree

### Name

FcStrFree — free a string

### Synopsis

```
#include <fontconfig.h>

void FcStrFree(FcChar8 *s);
```

### Description

This is just a wrapper around `free(3)` which helps track memory usage of strings within the fontconfig library.

### Version

Fontconfig version 2.6.99.behdad.20090508

## FcStrDirname

### Name

FcStrDirname — directory part of filename

### Synopsis

```
#include <fontconfig.h>

FcChar8 * FcStrDirname(const FcChar8 *file);
```

## Description

Returns the directory containing *file*. This is returned in newly allocated storage which should be freed when no longer needed.

## Version

Fontconfig version 2.6.99.behdad.20090508

# FcStrBasename

## Name

FcStrBasename — last component of filename

## Synopsis

```
#include <fontconfig.h>

FcChar8 * FcStrBasename(const FcChar8 *file);
```

## Description

Returns the filename of *file* stripped of any leading directory names. This is returned in newly allocated storage which should be freed when no longer needed.

## Version

Fontconfig version 2.6.99.behdad.20090508

