

The floatpag package

Vytas Statulevičius

vytas@vtex.lt

<http://www.vtex.lt/tex/download/macros/>

1999/04/29

1 Purpose:

provides commands to apply different pagestyles to the full page floats.

2 Usage:

`\floatpagestyle{<foo>}` will apply pagestyle ‘<foo>’ to all pages occupied by full page floats.

`\rotfloatpagestyle{<foo>}` will apply pagestyle ‘<foo>’ to all pages occupied by sideways figures and tables produced with the help of ‘rotating.sty’ package (Sebastian Rahtz and Leonor Barroca)

`\thisfloatpagestyle{<foo>}` will apply pagestyle ‘<foo>’ to a page where this command was used inside figure or table environment

3 Default:

`\floatpagestyle{headings}`

`\rotfloatpagestyle{plain}`

The macros, developed by Sigitas Tolusis <sigitas@vtex.lt>, were used in this package.

The following commands from the LaTeX2e kernel were redefined:

`\@xfloat`, `\@vtryfc`

The following command from the rotating.sty was redefined:

`\@xrotfloat`

`floatpag.sty`

Copyright 1999 V. Statulevičius

VTeX Ltd., Akademijos 4, Vilnius, Lithuania

e-mail vytas@vtex.lt

<http://www.vtex.lt/tex/download/macros/>

This program can be redistributed and/or modified under the terms of the L^AT_EX Project Public License Distributed from CTAN archives in directory `macros/latex/base/lppl.txt`; either version 1 of the License, or (at your option) any later version.